

GME® 4AEX SHIELD

GME® 4AEX SHIELDS

The new GME® Aluminum Extruded Trench Shield is a rugged, 4" wall shield that comes standard with a tough, T-6 knife edge and rugged top cap. Massive, extruded end members insure strength. Because it's aluminum, 4AEX can be handled by today's lighter excavators, allowing you to match your equipment to the proper machine.

FEATURES

- Rugged collar adapters for 5" pipe spreaders
- Lifting eyes
- Optional "no-knife edge" with heavy-duty skid plate
- Standard lengths to 16 feet
- Custom lengths on request
- Certified by a registered professional engineer to meet OSHA standards



**Standard Features Include
Knife Edge and Top Cap!**

GME® 4AEX SHIELD

4AEX – 4" ALUMINUM EXTRUDED WALL									
MODEL	SIZE			WEIGHT (LBS)	PIPE CLEARANCE	MAXIMUM DEPTH PER SOIL TYPE (FT.)			
	H	L	W			A	B	C-60	C-80
4AEX-68	6'	8'	4"	1438	36"	117	66	50	37
4AEX-610	6'	10'	4"	1708	36"	72	41	31	23
4AEX-612	6'	12'	4"	2050	36"	49	28	21	16
4AEX-614	6'	14'	4"	2301	36"	35	20	16	10
4AEX-616	6'	16'	4"	2539	36"	26	15	12	9
4AEX-88	8'	8'	4"	1736	48"	69	39	30	23
4AEX-810	8'	10'	4"	2195	48"	55	31	24	18
4AEX-812	8'	12'	4"	2631	48"	45	26	20	15
4AEX-814	8'	14'	4"	2937	48"	35	20	16	10
4AEX-816	8'	16'	4"	3197	48"	26	15	12	9

NOTE: 4AEX shields come standard with knife edge & protective top cap.

ACCESSORIES

5DS Spreader Sets: Loose 5" Schedule 80 Pipe														
Model	5DS24	5DS30	5DS36	5DS42	5DS48	5DS54	5DS60	5DS72	5DS84	5DS96	5DS108	5DS120	5DS132	5DS144
Inside Width	24"	30"	36"	42"	48"	54"	60"	72"	84"	96"	108"	120"	132"	144"
Wt. (lbs)	198	257	300	343	386	430	473	559	646	732	819	905	991	1078

NOTE: Four spreaders required per shield.

HEAVY-DUTY ADJUSTABLE SPREADERS AVAILABLE ON REQUEST.

4AEX LIFT & STACK ACCESSORIES	
MODEL	WT. (LBS.)
Nylon Sling – 6-ft.	7
Nylon Sling – 8-ft.	9
4AEX-SP Stacking pins (4)24" (incl. bolts)	20