

2AEX

Lightweight Aluminum Trench Shield

GME 2AEX SHIELDS

The GME 2AEX Shield is an aluminum extruded shield with a slim, 2" wall that comes standard with a tough, T-6 knife edge and rugged top cap. Massive, extruded end members ensure strength. Available in lengths up to 12-feet, it is sized for rubber-tired backhoes, and priced competitively.

OPTIONS

- Standard square-box tubing struts
- End loading struts
- 5" Schedule-80 pipe
- Screw-jack type struts
- Lifting eyes and bridle
- Pull bar
- Knife-Edge or No Knife-Edge
- Certified by a registered professional engineer to meet OSHA standards



2AEX - 2" ALUMINUM EXTRUDED WALL									
Model	H	Size		Weight (lbs.)	Pipe Clearance	Maximum Depth Per Soil Type (ft.)			
		L	W			A	B	C-60	C-80
2AEX-66	6'	6'	2"	724	30"	68	38	28	21
2AEX-68	6'	8'	2"	906	30"	58	32	24	18
2AEX-610	6'	10'	2"	1,088	30"	34	19	14	11
2AEX-612	6'	12'	2"	1,270	30"	24	13	10	8
2AEX-86	8'	6'	2"	943	36"	55	31	23	17
2AEX-88	8'	8'	2"	1,177	36"	55	31	23	17
2AEX-810	8'	10'	2"	1,412	36"	34	19	14	11
2AEX-812	8'	12'	2"	1,647	36"	24	13	10	8

NOTE: 2AEX Boxes come standard with Knife-Edge and protective top cap. Optional No Knife-Edge panels are available.

GME 2AEX SHIELD SPREADER SETS		
Model	Range	Weight (lbs.)
2AEX-AB	ADAPT BRCKTS	64
2AEX-2640	26" - 40"	28
2AEX-3250	32" - 50"	34
2AEX-3859	38" - 59"	41
2AEX-4468	44" - 68"	47
2AEX-5692	56" - 92"	62

END-LOADABLE STRUTS		
Model	Range	Weight (lbs.)
2AE X-SS-AB	ADAPT BRCKTS	80
2AEX-SS-2640	26" - 40"	54
2AEX-SS-3250	32" - 50"	66
2AEX-SS-3859	38" - 59"	78
2AEX-SS-4468	44" - 68"	92
2AE X-SS-5692	56" - 92"	114

LITE-SHIELD™ STRUTS		
Model	Range	Weight (lbs.)
LSS-AB	ADAPT BRCKTS	64
24LSS-1	24" - 32"	12
24LSS-2	32" - 48"	16
24LSS-2.5	40" - 64"	21
24LSS-3	51" - 86"	25

2AEX PULL BARS		
Model	Range	Weight (lbs.)
2AEX-PB-40	26" - 40"	26
2AEX-PB-50	32" - 50"	32
2AEX-PB-59	38" - 59"	41
2AEX-PB-68	44" - 68"	54
2AEX-PB-92	56" - 92"	62

2AEX LIFT & STACK ACCESSORIES		Weight (lbs.)
Model		
2AEX-LE Lift Eye Set (4)		24
Nylon Sling - 6-ft.		7
Nylon Sling - 8-ft.		9
2AEX-SP Stacking pins (4) 12' (incl. bolts)		20
2AEX-PB-92		62

NOTE: Pull bars come with built-in Lift Eyes (2). Extra 1/2 set Lift Eyes are required with Pull Bar.

5" Schedule-80 steel spreader pipe also available as an option