

Lite-Shield™

Lightweight Aluminum Trench Shield

GME LITE-SHIELD™ 24

The Lite-Shield™ 24 Series offers you a wide choice of panel lengths, from 2 to 12 feet. The lightweight 24-inch panels can be transported easily, even in a pick-up.

The system assembles in just minutes at the jobsite. Tongue-in-groove panels are easily aligned, and mechanical screw-jack struts provide fast, variable adjustment. For maximum versatility, the system can be used as a two, three, or four-sided configuration.


FEATURES

- Strong yet lightweight 6061-T6 aluminum construction
- 2-inch wall thickness
- Foam filling available as an option
- Unique keyed locking pin requires no keepers
- Certified by a professional engineer to meet OSHA standards
- Made in U.S.A.

LITE-SHIELD™ 24 PANELS		
Model	Dimensions (L x H x W)	Weight (lbs.)
24LSP-3	36" x 24" x 2"	45
24LSP-4	48" x 24" x 2"	63
24LSP-5	60" x 24" x 2"	75
24LSP-6	72" x 24" x 2"	86
24LSP-8	96" x 24" x 2"	114
24LSP-10	120" x 24" x 2"	140
24LSP-12	144" x 24" x 2"	155

SHIELDING SYSTEM CAPACITY DEPTH CHART				
Model	Maximum Depth Per Soil Type (ft.)			
	A	B	C-60	C-80
24LSP-3	50	50	40	30
24LSP-4	50	50	40	30
24LSP-5	50	50	40	30
24LSP-6	50	34	31	22
24LSP-8	50	32	24	18
24LSP-10	33	20	14	11
24LSP-12	23	13	10	7

MAXIMUM VERTICAL PIPE CLEARANCE = 24 INCHES



3-SIDED LITE-SHIELD™ 24



4-SIDED LITE-SHIELD™ 24



2-SIDED LITE-SHIELD™ 24 W/ PULLBAR